

LG Electronics Inc. % Jonghyun Kim Chief Consultant GMS Consulting 4th Floor, Digital Cube, 34, Sangamsan-ro Seoul, Mapo-gu 03909 KOREA

Re: K221061 June 3, 2022

Trade/Device Name: 21HQ613D Regulation Number: 21 CFR 892.2050

Regulation Name: Medical image management and processing system

Regulatory Class: Class II

Product Code: PGY Dated: April 7, 2022 Received: April 11, 2022

## Dear Jonghyun Kim:

We have reviewed your Section 510(k) premarket notification of intent to market the device referenced above and have determined the device is substantially equivalent (for the indications for use stated in the enclosure) to legally marketed predicate devices marketed in interstate commerce prior to May 28, 1976, the enactment date of the Medical Device Amendments, or to devices that have been reclassified in accordance with the provisions of the Federal Food, Drug, and Cosmetic Act (Act) that do not require approval of a premarket approval application (PMA). You may, therefore, market the device, subject to the general controls provisions of the Act. Although this letter refers to your product as a device, please be aware that some cleared products may instead be combination products. The 510(k) Premarket Notification Database located at <a href="https://www.accessdata.fda.gov/scripts/cdrh/cfdocs/cfpmn/pmn.cfm">https://www.accessdata.fda.gov/scripts/cdrh/cfdocs/cfpmn/pmn.cfm</a> identifies combination product submissions. The general controls provisions of the Act include requirements for annual registration, listing of devices, good manufacturing practice, labeling, and prohibitions against misbranding and adulteration. Please note: CDRH does not evaluate information related to contract liability warranties. We remind you, however, that device labeling must be truthful and not misleading.

If your device is classified (see above) into either class II (Special Controls) or class III (PMA), it may be subject to additional controls. Existing major regulations affecting your device can be found in the Code of Federal Regulations, Title 21, Parts 800 to 898. In addition, FDA may publish further announcements concerning your device in the <u>Federal Register</u>.

Please be advised that FDA's issuance of a substantial equivalence determination does not mean that FDA has made a determination that your device complies with other requirements of the Act or any Federal statutes and regulations administered by other Federal agencies. You must comply with all the Act's requirements, including, but not limited to: registration and listing (21 CFR Part 807); labeling (21 CFR Part

801); medical device reporting (reporting of medical device-related adverse events) (21 CFR 803) for devices or postmarketing safety reporting (21 CFR 4, Subpart B) for combination products (see <a href="https://www.fda.gov/combination-products/guidance-regulatory-information/postmarketing-safety-reporting-combination-products">https://www.fda.gov/combination-products/guidance-regulatory-information/postmarketing-safety-reporting-combination-products</a>); good manufacturing practice requirements as set forth in the quality systems (QS) regulation (21 CFR Part 820) for devices or current good manufacturing practices (21 CFR 4, Subpart A) for combination products; and, if applicable, the electronic product radiation control provisions (Sections 531-542 of the Act); 21 CFR 1000-1050.

Also, please note the regulation entitled, "Misbranding by reference to premarket notification" (21 CFR Part 807.97). For questions regarding the reporting of adverse events under the MDR regulation (21 CFR Part 803), please go to <a href="https://www.fda.gov/medical-devices/medical-device-safety/medical-device-reporting-mdr-how-report-medical-device-problems">https://www.fda.gov/medical-device-problems</a>.

For comprehensive regulatory information about medical devices and radiation-emitting products, including information about labeling regulations, please see Device Advice (<a href="https://www.fda.gov/medical-devices/device-advice-comprehensive-regulatory-assistance">https://www.fda.gov/medical-devices/device-advice-comprehensive-regulatory-assistance</a>) and CDRH Learn (<a href="https://www.fda.gov/training-and-continuing-education/cdrh-learn">https://www.fda.gov/training-and-continuing-education/cdrh-learn</a>). Additionally, you may contact the Division of Industry and Consumer Education (DICE) to ask a question about a specific regulatory topic. See the DICE website (<a href="https://www.fda.gov/medical-devices/device-advice-comprehensive-regulatory-assistance/contact-us-division-industry-and-consumer-education-dice">https://www.fda.gov/medical-devices/device-advice-comprehensive-regulatory-assistance/contact-us-division-industry-and-consumer-education-dice">https://www.fda.gov/medical-devices/device-advice-comprehensive-regulatory-assistance/contact-us-division-industry-and-consumer-education-dice</a>) for more information or contact DICE by email (DICE@fda.hhs.gov) or phone (1-800-638-2041 or 301-796-7100).

Sincerely,

For

Michael D. O'Hara, Ph.D.
Deputy Director
DHT 8C: Division of Radiological Imaging and Radiation Therapy Devices
OHT 8: Office of Radiological Health
Office of Product Evaluation and Quality
Center for Devices and Radiological Health

Enclosure

# DEPARTMENT OF HEALTH AND HUMAN SERVICES Food and Drug Administration

## **Indications for Use**

510(k) Number (if known)

Form Approved: OMB No. 0910-0120 Expiration Date: 06/30/2020

See PRA Statement below.

221061
evice Name IHQ613D
dications for Use (Describe) his Medical Monitor is indicated for use in displaying radiological images (including full-field digital ammography and digital breast tomosynthesis) for review, analysis, and diagnosis by trained medical ractitioners.
ype of Use (Select one or both, as applicable)
Prescription Use (Part 21 CFR 801 Subpart D) Over-The-Counter Use (21 CFR 801 Subpart C)

CONTINUE ON A SEPARATE PAGE IF NEEDED.

This section applies only to requirements of the Paperwork Reduction Act of 1995.

#### \*DO NOT SEND YOUR COMPLETED FORM TO THE PRA STAFF EMAIL ADDRESS BELOW.\*

The burden time for this collection of information is estimated to average 79 hours per response, including the time to review instructions, search existing data sources, gather and maintain the data needed and complete and review the collection of information. Send comments regarding this burden estimate or any other aspect of this information collection, including suggestions for reducing this burden, to:

Department of Health and Human Services Food and Drug Administration Office of Chief Information Officer Paperwork Reduction Act (PRA) Staff PRAStaff@fda.hhs.gov

"An agency may not conduct or sponsor, and a person is not required to respond to, a collection of information unless it displays a currently valid OMB number."

## 510(k) Summary

[As Required by 21 CFR 807.92]

## 1. Date Prepared [21 CFR 807.92(a)(a)]

April 07, 2022

#### 2. Submitter's Information [21 CFR 807.92(a)(1)]

• Name of Sponsor: LG Electronics Inc.

- Address: 222, LG-ro, Cheongho-ri, Jinwi-myeon, Pyeongtaek-si,

Gyeonggi-do, 17709, Republic of Korea

Contact Name: Jinhwan Jun / Chief Research Engineer

Telephone No.: +82-31-8066-5641Email Address: jinhwan.jun@lge.com

Name of Manufacturer:
 LG Electronics Inc.

- Address: 77, Sanho-daero, Gumi-si, Gyeongsangbuk-do, 39381,

Republic of Korea

## 3. Trade Name, Common Name, Classification [21 CFR 807.92(a)(2)]

Trade Name: 21HQ613DCommon Name: Medical Monitor

Classification:

Classification Name	Medical image management and processing system.
Classification Number	21 CFR 892.2050
Product Code	PGY
Device Class	II
Review Panel	Radiology

## 4. Identification of Predicate Device(s) [21 CFR 807.92(a)(3)]

The identified predicate devices within this submission are shown as follow;

#### **Primary Predicate Device**

• 510(k) Number: K172738

• Applicant: EIZO Corporation

Classification Name: Medical image management and processing system.

• Trade Name: RX560

#### **Predicate Device**

510(k) Number: K201777Applicant: LG Electronics

• Classification Name: Medical image management and processing system.

• Trade Name: 31HN713D

## 5. Description of the Device [21 CFR 807.92(a)(4)]

The Medical monitor is intended to provide high resolution color and grayscale medical imaging for PACS and Radiology system. This Medical Monitor is intended to be used by trained medical practitioners for displaying, reviewing, and analysis of medical images

## 6. Indications for use [21 CFR 807.92(a)(5)]

This Medical Monitor is indicated for use in displaying radiological images (including full-field digital mammography and digital breast tomosynthesis) for review, analysis, and diagnosis by trained medical practitioners.

## 7. Technological Characteristics (Equivalence to Predicate Device) [21 CFR 807.92(a)(6)]

The table below presents comparisons between the subject device (21HQ613D) and the legally marketed predicate devices (K172738 and K201777):

[Table 1. Comparison of Proposed Device to Primary Predicate Device]

K Number   Not known   K172738		Proposed Device	Primary Predicate Device	
Model Name       21HQ613D       RX560         Classification Name       Medical image management and processing system.       Medical image management and processing system.         Classification Number       21 CFR 892.2050       21 CFR 892.2050         Indications for Use       This Medical Monitor is indicated for use in displaying radiological images (including full-field digital mammography and digital breast tomosynthesis) for review, analysis, and diagnosis by trained medical practitioners.       This product is intended to be used in displaying and viewing digital images, including standard and multiframe digital mammography, for review, analysis and diagnosis by trained medical practitioners. It is specially designed for breast tomosynthesis applications.         Display Technology       The 21HQ613D has a TM213XDGP31 module for displaying. The TM213XDGP31 is a "TFT Liquid Crystal Display module with LED Backlight unit and one 30pin eDP port and 4ch-LVDS interface. This module supports 2048x2560 5M Pixel mode and can display color driven by 10bit drivers. The LCD module includes built-in converter for Backlight       This is a color LCD montifor for viewing angles and the matrix size (or resolution) is 2048x2560 pixels.         Power Consumption       MAX. 120W Off Mode ≤ 0.3W       87 W / Less than 1 W         Screen size       473.4 x 364.5 mm       337.9 mm x 422.4 mm         LCD Screen       TFT LCD       TFT LCD         Pixel Pitch       0.165 x 0.165 mm       0.165 x 0.165 mm         Resolution       2,048 x 2,560         Horizontal Frequenc	K Number	Number Not known K172738		
Classification Name       Medical image management and processing system.       Medical image management and processing system.         Classification Number       21 CFR 892.2050       21 CFR 892.2050         Indications for Use       This Medical Monitor is indicated for use in displaying radiological images (including full-field digital mammography and digital breast tomosynthesis) for review, analysis, and diagnosis by trained medical practitioners.       This product is intended to be used in displaying and viewing digital images, including standard and multiframe digital mammography, for review, analysis and diagnosis by trained medical practitioners. It is specially designed for breast tomosynthesis applications.         Display Technology       The 21HQ613D has a TM213XDGP31 module for displaying. The TM213XDGP31 is a "TFT Liquid Crystal Display module with LED Backlight unit and one 30pin eDP port and 4ch-LVDS interface. This module supports 2048x2560 5M Pixel mode and can display color driven by 10bit drivers. The LCD module includes built-in converter for Backlight       This is a color LCD monitor for viewing digital images, including standard and multiframe digital mammography, for review, analysis and diagnosis. The color panel employs in-plane switching (IPS) technology allowing wide viewing angles and the matrix size (or resolution) is 2048x2560 pixels.         Power Consumption       MAX. 120W Off Mode ≤ 0.3W       87 W / Less than 1 W         Screen size       473.4 x 364.5 mm       337.9 mm x 422.4 mm         LCD Screen       TFT LCD       TFT LCD         Pixel Pitch       0.165 x 0.165 mm       0.165 x 0.165 mm	Manufacturer	LG Electronics Inc.	EIZO Corporation	
Display Technology	Model Name	21HQ613D	RX560	
Classification Number   21 CFR 892.2050   21 CFR 892.2050   This Medical Monitor is indicated for use in displaying radiological images (including full-field digital mammography and digital breast tomosynthesis) for review, analysis, and diagnosis by trained medical practitioners.   The 21HQ613D has a TM213XDGP31 module for displaying. The TM213XDGP31 is a "TFT Liquid Crystal Display module with LED Backlight unit and one 30pin eDP port and 4ch-LVDS interface. This module supports 2048x2560 5M Pixel mode and can display color driven by 10bit drivers. The LCD module includes built-in converter for Backlight   MAX. 120W	Classification Name	Medical image management and	Medical image management and	
This Medical Monitor is indicated for use in displaying radiological images (including full-field digital mammography and digital breast tomosynthesis) for review, analysis, and diagnosis by trained medical practitioners.  Display Technology  The 21HQ613D has a TM213XDGP31 module for displaying. The TM213XDGP31 is a "TFT Liquid Crystal Display module with LED Backlight unit and one 30pin eDP port and 4ch-LVDS interface. This module supports 2048x2560 5M Pixel mode and can display color driven by 10bit drivers. The LCD module includes built-in converter for Backlight  Power Consumption  MAX. 120W Off Mode ≤ 0.3W  Screen size  473.4 x 364.5 mm CD Screen TFT LCD Pixel Pitch 0.165 x 0.165 mm Resolution  Resolution  This product is intended to be used in displaying and viewing digital images, including standard and multiframe digital mammography, for review, analysis and diagnosis. The color panel employs in-plane switching (IPS) technology allowing wide viewing angles and the matrix size (or resolution) is 2048x2560 pixels.  87 W / Less than 1 W  TFT LCD  TFT LCD  165 x 0.165 mm  2,048 x 2,560 pixels  31 kHz to 135 kHz		processing system.	processing system.	
in displaying radiological images (including full-field digital mammography and digital breast tomosynthesis) for review, analysis, and diagnosis by trained medical practitioners.  Display Technology  The 21HQ613D has a TM213XDGP31 module for displaying. The TM213XDGP31 is a "TFT Liquid Crystal Display module with LED Backlight unit and one 30pin eDP port and 4ch-LVDS interface. This module supports 2048x2560 5M Pixel mode and can display color driven by 10bit drivers. The LCD module includes built-in converter for Backlight  Power Consumption  MAX. 120W Off Mode ≤ 0.3W  Screen size 473.4 x 364.5 mm LCD Screen TFT LCD Pixel Pitch 0.165 x 0.165 mm Resolution  Idisplaying and viewing digital images, including standard and multiframe digital mammography, for review, analysis applications.  This is a color LCD monitor for viewing digital images, including standard and multiframe digital mammography, for review, analysis and diagnosis. The color panel employs in-plane switching (IPS) technology allowing wide viewing angles and the matrix size (or resolution) is 2048x2560 pixels.  87 W / Less than 1 W TFT LCD TFT LCD TFT LCD  Pixel Pitch 0.165 x 0.165 mm 0.165 x 0.165 mm Resolution 2,048 x 2,560 pixels 31 kHz to 135 kHz	Classification Number	21 CFR 892.2050	21 CFR 892.2050	
(including full-field digital mammography and digital breast tomosynthesis) for review, analysis, and diagnosis by trained medical practitioners.  Display Technology  The 21HQ613D has a TM213XDGP31 module for displaying. The TM213XDGP31 is a "TFT Liquid Crystal Display module with LED Backlight unit and one 30pin eDP port and 4ch-LVDS interface. This module supports 2048x2560 5M Pixel mode and can display color driven by 10bit drivers. The LCD module includes built-in converter for Backlight  Power Consumption  MAX. 120W Off Mode ≤ 0.3W  Screen size  473.4 x 364.5 mm  LCD Screen  TFT LCD  Pixel Pitch  0.165 x 0.165 mm  Resolution  (including standard and multiframe digital mammography, for review, analysis applications.  This is a color LCD monitor for viewing digital images, including standard and multiframe digital mammography, for review, analysis and diagnosis. The color panel employs in-plane switching (IPS) technology allowing wide viewing angles and the matrix size (or resolution) is 2048x2560 pixels.  87 W / Less than 1 W  TFT LCD  TFT LCD  TFT LCD  Pixel Pitch  0.165 x 0.165 mm  Resolution  2,048 x 2,560 pixels  31 kHz to 135 kHz	Indications for Use	This Medical Monitor is indicated for use	This product is intended to be used in	
and digital breast tomosynthesis) for review, analysis, and diagnosis by trained medical practitioners.  Display Technology  The 21HQ613D has a TM213XDGP31 module for displaying. The TM213XDGP31 is a "TFT Liquid Crystal Display module with LED Backlight unit and one 30pin eDP port and 4ch-LVDS interface. This module supports 2048x2560 5M Pixel mode and can display color driven by 10bit drivers. The LCD module includes built-in converter for Backlight  Power Consumption  Power Consumption  Power Consumption  AX. 120W  Off Mode ≤ 0.3W  Screen size  473.4 x 364.5 mm  LCD Screen  TFT LCD  Pixel Pitch  0.165 x 0.165 mm  Resolution  And diagnosis by trained diagnosis by trained diagnosis by trained medical practitioners. It is specially designed for breast tomosynthesis applications.  This is a color LCD monitor for viewing digital images, including standard and multiframe digital mammography, for review, analysis and diagnosis by trained medical practitioners. It is specially designed for breast tomosynthesis applications.  This is a color LCD monitor for viewing digital images, including standard and multiframe digital mammography, for review, analysis and diagnosis by trained medical practitioners. It is specially designed for breast tomosynthesis applications.  This is a color LCD monitor for viewing digital images, including standard and multiframe digital mammography, for review, analysis and diagnosis by trained medical practitioners. It is specially designed for breast tomosynthesis applications.  This is a color LCD monitor for viewing digital images, including standard and multiframe digital mammography, for review, analysis and diagnosis. The color panel employs in-plane switching (IPS) technology allowing wide viewing angles and the matrix size (or resolution) is 2048x2560 pixels.  2048x2560 pixels.  87 W / Less than 1 W  TFT LCD  TFT LCD  Pixel Pitch  0.165 x 0.165 mm  37.9 mm x 422.4 mm  1055 x 0.165 mm  2,048 x 2,560 pixels  31 kHz to 135 kHz				
review, analysis, and diagnosis by trained medical practitioners.  Display Technology  The 21HQ613D has a TM213XDGP31 module for displaying. The TM213XDGP31 is a "TFT Liquid Crystal Display module with LED Backlight unit and one 30pin eDP port and 4ch-LVDS interface. This module supports 2048x2560 5M Pixel mode and can display color driven by 10bit drivers. The LCD module includes built-in converter for Backlight  Power Consumption  MAX. 120W Off Mode ≤ 0.3W  Screen size  473.4 x 364.5 mm  LCD Screen  TFT LCD  Pixel Pitch  Resolution  review, analysis and diagnosis by trained medical practitioners. It is specially designed for breast tomosynthesis applications.  This is a color LCD monitor for viewing digital images, including standard and multiframe digital mammography, for review, analysis and diagnosis. The color panel employs in-plane switching (IPS) technology allowing wide viewing angles and the matrix size (or resolution) is 2048x2560 pixels.  87 W / Less than 1 W  TFT LCD  TFT LCD  Pixel Pitch  0.165 x 0.165 mm  Resolution  2,048 x 2,560 pixels  31 kHz to 135 kHz				
medical practitioners.  Display Technology  The 21HQ613D has a TM213XDGP31 module for displaying. The TM213XDGP31 is a "TFT Liquid Crystal Display module with LED Backlight unit and one 30pin eDP port and 4ch-LVDS interface. This module supports 2048x2560 5M Pixel mode and can display color driven by 10bit drivers. The LCD module includes built-in converter for Backlight  Power Consumption  MAX. 120W Off Mode ≤ 0.3W  Screen size 473.4 x 364.5 mm  LCD Screen TFT LCD  Pixel Pitch 0.165 x 0.165 mm  Resolution  Medical practitioners. It is specially designed for breast tomosynthesis applications.  This is a color LCD monitor for viewing digital images, including standard and multiframe digital mammography, for review, analysis and diagnosis. The color panel employs in-plane switching (IPS) technology allowing wide viewing angles and the matrix size (or resolution) is 2048x2560 pixels.  87 W / Less than 1 W  TFT LCD  TFT LCD  TFT LCD  TFT LCD  77				
Display Technology  The 21HQ613D has a TM213XDGP31 module for displaying. The TM213XDGP31 is a "TFT Liquid Crystal Display module with LED Backlight unit and one 30pin eDP port and 4ch-LVDS interface. This module supports 2048x2560 5M Pixel mode and can display color driven by 10bit drivers. The LCD module includes built-in converter for Backlight  Power Consumption  MAX. 120W Off Mode $\leq$ 0.3W  Screen size 473.4 x 364.5 mm  LCD Screen  TFT LCD  Pixel Pitch 0.165 x 0.165 mm  Resolution  Possible Technology  This is a color LCD monitor for viewing digital images, including standard and multiframe digital mammography, for review, analysis and diagnosis. The color panel employs in-plane switching (IPS) technology allowing wide viewing angles and the matrix size (or resolution) is 2048x2560 pixels.  87 W / Less than 1 W  TFT LCD  TFT LCD  TFT LCD  75 LCD  76 Sx 0.165 mm  0.165 x 0.165 mm  Resolution  2,048 x 2,560 pixels  31 kHz to 135 kHz				
Display TechnologyThe 21HQ613D has a TM213XDGP31 module for displaying. The TM213XDGP31 is a "TFT Liquid Crystal Display module with LED Backlight unit and one 30pin eDP port and 4ch-LVDS interface. This module supports 2048x2560 5M Pixel mode and can display color driven by 10bit drivers. The LCD module includes built-in converter for BacklightThis is a color LCD monitor for viewing digital images, including standard and multiframe digital mammography, for review, analysis and diagnosis. The color panel employs in-plane switching (IPS) technology allowing wide viewing angles and the matrix size (or resolution) is 2048x2560 pixels.Power ConsumptionMAX. 120W Off Mode ≤ 0.3W87 W / Less than 1 WScreen size473.4 x 364.5 mm337.9 mm x 422.4 mmLCD ScreenTFT LCDTFT LCDPixel Pitch0.165 x 0.165 mm0.165 x 0.165 mmResolution2,048 x 2,560 pixels2,048 x 2,560Horizontal Frequency30 kHz to 135kHz31 kHz to 135 kHz		medical practitioners.	. , ,	
module for displaying. The TM213XDGP31 is a "TFT Liquid Crystal Display module with LED Backlight unit and one 30pin eDP port and 4ch-LVDS interface. This module supports 2048x2560 5M Pixel mode and can display color driven by 10bit drivers. The LCD module includes built-in converter for Backlight  Power Consumption  MAX. 120W Off Mode $\leq 0.3$ W  Screen size 473.4 x 364.5 mm  LCD Screen TFT LCD  Pixel Pitch 0.165 x 0.165 mm  Resolution digital images, including standard and multiframe digital mammography, for review, analysis and diagnosis. The color panel employs in-plane switching (IPS) technology allowing wide viewing angles and the matrix size (or resolution) is 2048x2560 pixels.  87 W / Less than 1 W  TFT LCD  TFT LCD  TFT LCD  7 Screen Size 473.4 x 364.5 mm  1 337.9 mm x 422.4 mm  TFT LCD  9 ixel Pitch 0.165 x 0.165 mm  2,048 x 2,560 pixels  Horizontal Frequency 30 kHz to 135kHz  2 digital images, including standard and multiframe digital mammography, for review, analysis and diagnosis. The color panel employs in-plane switching (IPS) technology allowing wide viewing angles and the matrix size (or resolution) is 2048x2560 pixels.				
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	Display Technology			
Display module with LED Backlight unit and one 30pin eDP port and 4ch-LVDS interface. This module supports 2048x2560 5M Pixel mode and can display color driven by 10bit drivers. The LCD module includes built-in converter for Backlight  Power Consumption  MAX. 120W Off Mode $\leq$ 0.3W  Screen size 473.4 x 364.5 mm  LCD Screen  TFT LCD  Pixel Pitch 0.165 x 0.165 mm  Resolution Display module with LED Backlight unit and one 30pin eDP port and 4ch-LVDS interface. The panel employs in-plane switching (IPS) technology allowing wide viewing angles and the matrix size (or resolution) is 2048x2560 pixels.  87 W / Less than 1 W  TFT LCD  TFT LCD  TFT LCD  0.165 x 0.165 mm  2,048 x 2,560 pixels  37 W / Less than 1 W  37 W / Less than 1 W  TFT LCD  TFT LCD  TFT LCD  10 0.165 x 0.165 mm  2,048 x 2,560 pixels  31 kHz to 135 kHz				
and one 30pin eDP port and 4ch-LVDS interface. This module supports 2048x2560 5M Pixel mode and can display color driven by 10bit drivers. The LCD module includes built-in converter for Backlight  Power Consumption  MAX. 120W Off Mode $\leq 0.3$ W  Screen size 473.4 x 364.5 mm  LCD Screen  TFT LCD  Pixel Pitch 0.165 x 0.165 mm  Resolution 2,048 x 2,560 pixels  panel employs in-plane switching (IPS) technology allowing wide viewing angles and the matrix size (or resolution) is 2048x2560 pixels.  87 W / Less than 1 W  TFT LCD  TFT LCD  TFT LCD  0.165 x 0.165 mm  0.165 x 0.165 mm  2,048 x 2,560 pixels  30 kHz to 135kHz  31 kHz to 135 kHz			5 1 77	
interface. This module supports 2048x2560 5M Pixel mode and can display color driven by 10bit drivers. The LCD module includes built-in converter for Backlight  Power Consumption  MAX. 120W Off Mode $\leq 0.3$ W  Screen size 473.4 x 364.5 mm  LCD Screen TFT LCD  Pixel Pitch 0.165 x 0.165 mm  Resolution 2,048 x 2,560 pixels  interface. This module supports and the matrix size (or resolution) is 2048x2560 pixels.  87 W / Less than 1 W  337.9 mm x 422.4 mm  TFT LCD  TFT LCD  0.165 x 0.165 mm  0.165 x 0.165 mm  2,048 x 2,560 pixels  30 kHz to 135kHz  31 kHz to 135 kHz				
$ \begin{array}{c} 2048x2560 \; \text{5M Pixel mode and can} \\ \text{display color driven by 10bit drivers. The} \\ \text{LCD module includes built-in converter} \\ \text{for Backlight} \\ \end{array} \begin{array}{c} \text{Power Consumption} \\ \text{Screen size} \\ \text{473.4 x 364.5 mm} \\ \text{LCD Screen} \\ \end{array} \begin{array}{c} \text{TFT LCD} \\ \text{Pixel Pitch} \\ \text{Resolution} \\ \end{array} \begin{array}{c} \text{337.9 mm x 422.4 mm} \\ \text{TFT LCD} \\ \text{TFT LCD} \\ \text{O.165 x 0.165 mm} \\ \text{Resolution} \\ \text{2,048 x 2,560 pixels} \\ \text{30 kHz to 135kHz} \\ \end{array} \begin{array}{c} \text{31 kHz to 135 kHz} \\ \end{array} $				
display color driven by 10bit drivers. The LCD module includes built-in converter for Backlight  Power Consumption  MAX. 120W  Off Mode $\leq 0.3W$ Screen size  473.4 x 364.5 mm  100 Screen  TFT LCD  Pixel Pitch  Resolution  2048x2560 pixels.  2048x2560 pixels.  2048x2560 pixels.  2048x2560 pixels.  87 W / Less than 1 W  TFT LCD  TFT LCD  TFT LCD  7 TFT LCD  0.165 x 0.165 mm  0.165 x 0.165 mm  2,048 x 2,560 pixels  30 kHz to 135kHz  31 kHz to 135 kHz				
LCD module includes built-in converter for Backlight87 W / Less than 1 WPower ConsumptionMAX. 120W Off Mode ≤ 0.3W87 W / Less than 1 WScreen size $473.4 \times 364.5 \text{ mm}$ $337.9 \text{ mm} \times 422.4 \text{ mm}$ LCD ScreenTFT LCDTFT LCDPixel Pitch $0.165 \times 0.165 \text{ mm}$ $0.165 \times 0.165 \text{ mm}$ Resolution $2,048 \times 2,560 \text{ pixels}$ $2,048 \times 2,560 \text{ mm}$ Horizontal Frequency $30 \text{ kHz to } 135 \text{ kHz}$ $31 \text{ kHz to } 135 \text{ kHz}$				
for Backlight         Power Consumption       MAX. 120W       87 W / Less than 1 W         Off Mode ≤ 0.3W       337.9 mm x 422.4 mm         Screen size       473.4 x 364.5 mm       337.9 mm x 422.4 mm         LCD Screen       TFT LCD       TFT LCD         Pixel Pitch       0.165 x 0.165 mm       0.165 x 0.165 mm         Resolution       2,048 x 2,560 pixels       2,048 x 2,560         Horizontal Frequency       30 kHz to 135kHz       31 kHz to 135 kHz			2048X2560 pixeis.	
Power Consumption       MAX. 120W Off Mode ≤ 0.3W       87 W / Less than 1 W         Screen size       473.4 x 364.5 mm       337.9 mm x 422.4 mm         LCD Screen       TFT LCD       TFT LCD         Pixel Pitch       0.165 x 0.165 mm       0.165 x 0.165 mm         Resolution       2,048 x 2,560 pixels       2,048 x 2,560         Horizontal Frequency       30 kHz to 135kHz       31 kHz to 135 kHz				
Off Mode ≤ $0.3W$ Screen size $473.4 \times 364.5 \text{ mm}$ $337.9 \text{ mm} \times 422.4 \text{ mm}$ LCD Screen       TFT LCD       TFT LCD         Pixel Pitch $0.165 \times 0.165 \text{ mm}$ $0.165 \times 0.165 \text{ mm}$ Resolution $2,048 \times 2,560 \text{ pixels}$ $2,048 \times 2,560 \text{ mm}$ Horizontal Frequency $30 \text{ kHz to } 135 \text{ kHz}$ $31 \text{ kHz to } 135 \text{ kHz}$	Dower Consumption		97 W / Loss than 1 W	
Screen size         473.4 x 364.5 mm         337.9 mm x 422.4 mm           LCD Screen         TFT LCD         TFT LCD           Pixel Pitch         0.165 x 0.165 mm         0.165 x 0.165 mm           Resolution         2,048 x 2,560 pixels         2,048 x 2,560           Horizontal Frequency         30 kHz to 135kHz         31 kHz to 135 kHz	Power Consumption		07 W / Less than 1 W	
LCD Screen         TFT LCD         TFT LCD           Pixel Pitch         0.165 x 0.165 mm         0.165 x 0.165 mm           Resolution         2,048 x 2,560 pixels         2,048 x 2,560           Horizontal Frequency         30 kHz to 135kHz         31 kHz to 135 kHz	Scroon sizo		227.0 mm v 422.4 mm	
Pixel Pitch         0.165 x 0.165 mm         0.165 x 0.165 mm           Resolution         2,048 x 2,560 pixels         2,048 x 2,560           Horizontal Frequency         30 kHz to 135kHz         31 kHz to 135 kHz				
Resolution         2,048 x 2,560 pixels         2,048 x 2,560           Horizontal Frequency         30 kHz to 135kHz         31 kHz to 135 kHz		-		
Horizontal Frequency 30 kHz to 135kHz 31 kHz to 135 kHz				
Input video signals DVI IN x 1, DVI x 1				
DP IN x 2	input viuco signais	· ·		
DP OUT x 1 DP OUT x 1				

The comparison table shows that the subject device (21HQ613D) has the similar indications for use the primary predicate device. Although the devices have some different technological characteristics (screen size, pixel pitch, Resolution, horizontal/vertical frequency and input video signals), these differences do not make the subject device less safe and reliable, so the subject device fits for diagnostic use as the predicate device does. There are no significant differences in the technological characteristics of the subject device. All the differences between the subject and predicate device do not raise different questions of safety and effectiveness. It is substantially equivalent to a predicate device in indications for use and technology characteristics.

[Table 2. Comparison of Proposed Device to Predicate Device]

	Proposed Device	Predicate Device
K Number	Not known	K201777
Manufacturer	LG Electronics Inc.	LG Electronics Inc.
Model Name	21HQ613D	31HN713D
Classification Name	Medical image management and	Medical image management and
	processing system.	processing system.
Classification Number	21 CFR 892.2050	21 CFR 892.2050
Indications for Use	This Medical Monitor is indicated for use	This Medical Monitor is indicated for use
	in displaying radiological images	in displaying radiological images
	(including full-field digital mammography	(including full-field digital mammography
	and digital breast tomosynthesis) for	and digital breast tomosynthesis) for
	review, analysis, and diagnosis by trained	review, analysis, and diagnosis by trained
	medical practitioners.	medical practitioners.
Display Technology	The 21HQ613D has a TM213XDGP31	The 31HN713D has a LB310FTM module
	module for displaying. The	for displaying. The LB310FTM is a 31"
	TM213XDGP31 is a " TFT Liquid Crystal	TFT Liquid Crystal Display module with
	Display module with LED Backlight unit	LED Backlight unit. This module supports
	and one 30pin eDP port and 4ch-LVDS	4,200 x 2,800 pixels and can display
	interface. This module supports	color driven by 10bit drivers.
	2048x2560 5M Pixel mode and can	
	display color driven by 10bit drivers. The	
	LCD module includes built-in converter	
D 0 11	for Backlight	MAY 450W
Power Consumption	MAX. 120W	MAX. 150W
	Off Mode ≤ 0.3W	Sleep Mode ≤ 0.5W
	472.4. 264.5	Off Mode ≤ 0.3W
Screen size	473.4 x 364.5 mm	676.9 x 459.7 mm
LCD Screen	TFT LCD	TFT LCD
Pixel Pitch	0.165 x 0.165 mm	0.1554 x 0.1554 mm
Resolution	2,048 x 2,560 pixels	4,200 x 2,800 pixels
Horizontal Frequency	30 kHz to 135kHz	30 kHz to 135kHz
Vertical Frequency	24 Hz to 61 Hz	56 Hz to 61 Hz
Input video signals	DVI IN x 1,	DisplayPort x 2
	DP IN x 2	HDMI x 1
	DP OUT x 1	

The comparison table shows that the subject device (21HQ613D) has the similar indications for use the predicate device. Although the devices have some different technological characteristics (screen size, pixel pitch, Resolution, horizontal/vertical frequency and input video signals), these differences do not make the subject device less safe and reliable, so the subject device fits for diagnostic use as the predicate device does. There are no significant differences in the technological characteristics of the subject device. All the differences between the subject and predicate device do not raise different questions of safety and effectiveness. It is substantially equivalent to a predicate device in indications for use and technology characteristics.

#### 8. Non-Clinical Test summary

1) Electrical Safety and Electromagnetic Compatibility

The test results demonstrated that the proposed device complies with the following standards:

- Electrical Basic Safety and Essential Performance requirements in accordance with IEC 60601-1:2005/AMD1:2012
- Electromagnetic Compatibility Testing in accordance with IEC 60601-1-2 Edition 4.0:2014
- Medical Electrical Equipment Part 1-6: General Requirements for Basic Safety and Essential Performance - Collateral Standard: Usability in accordance with IEC 60601-1-6:2010/A1:2013

#### 2) Software Validation

The 21HQ613D contains MODERATE level of concern software. The software was designed and developed according to a software development process and was verified and validated.

The software information is provided in accordance with FDA guidance: The content of premarket submissions for software contained in medical devices, on May 11, 2005.

#### 3) Guidance

Display Devices for Diagnostic Radiology – Guidance for Industry and Food and Drug Administration Staff, issued on October 2, 2017

According to the guidance, we test following performance items:

	Measurements	Description	SE Note
a.	Spatial resolution	Measurements of the transfer of information from the image data to the luminance fields at different spatial frequencies of interest typically done by reporting the modulation transfer function. Non-isotropic resolution properties should be characterized properly by providing two-dimensional measurements or measurements along at least two representative axes. (Using TG18 QC Test Pattern)	Equivalent
b.	Pixel defects	Measurements (count, types (e.g., sub- pixel or entire pixel, always-on, always- off), and locations (map) of pixel defects. This is typically provided as a tolerance limit. Pixel defects can interfere with the visibility of small details in medical images.	Equivalent
C.	Artifacts	Evaluate for image artifacts such as ghosting and/or image sticking from displaying a fixed test pattern for a period of time.  (Using 5x5 mosaic pattern, 64Gray / 127 Gray judgment)	Same
d.	Temporal response	Measurements of the temporal behavior of the display in responding to changes in image values from frame to frame. Since these transitions are typically not symmetric, rise and fall time constants	Equivalent

	Measurements	Description	SE Note
	Luminana	are needed to characterize the system.  Slow displays can alter details and contrast of the image when large image stacks are browsed or in video, panning, and zooming modes.  Measurements of the maximum and	Same
e.	Luminance	minimum luminance that the device outputs as used in the application under recommended conditions and the achievable values if the device is set to expand the range to the limit.	Same
f.	Conformance to a grayscale-to-luminance function	Measurements of the mapping between image values and the luminance output following a target model response for 256 or more levels.	Equivalent
g.	Luminance at 30° and 45° in diagonal, horizontal, and vertical directions at center and four corners	Measurements of the luminance response at off-normal viewing related to the target model for the luminance response.	Equivalent
h.	Luminance uniformity or Mura test	Measurements of the uniformity of the luminance across the display screen.	Equivalent
i.	Stability of luminance and chromaticity response with temperature and time of operation (on-time)	Measurements of the change in luminance and chromaticity response with temperature and use time.	Same
j.	Spatial noise	Measurements of the spatial noise level as represented by the noise power spectrum using an appropriate ratio of camera and display pixels. Spatial noise and resolution affect the way images are presented to the viewer and can alter features that are relevant to the interpretation process of the physician or radiologist.	Equivalent
k.	Reflection coefficient	Measurements of the reflection coefficients of the display device. Specular and diffuse reflection coefficients can be used as surrogates for the full bidirectional reflection distribution function.	Same
l.	Veiling glare or small-spot contrast	Measurements of the contrast obtained for small targets.	Equivalent
m.	<b>.</b>	Chromaticity at different luminance levels of primary colors as indicated by the color coordinates in an appropriate units system (e.g., CIE u'v') and the color gamut enveloped by the primary colors.	Equivalent
n.	Gray tracking	Chromaticity at different luminance levels of gray shades, including the white point, as indicated by the color coordinates in an appropriate units system	Equivalent

According to the above test results, there are no significant performance differences between 21HQ613D and the predicate devices that would adversely affect the use of the product. It has substantially equivalent performance compared to the predicate devices.

#### **Clinical Test Summary:**

No clinical studies were considered necessary and performed.

## 9. Conclusion [21 CFR 807.92(b)(3)]

In according with the Federal Food & Drug and cosmetic Act, 21 CFR Part 807, and based on the information provided in this premarket notification LG Electronics, concludes that the 21HQ613D is substantially equivalent in safety and effectiveness to the predicate devices as described herein.